

## 1. Product and company identification

**Product name** : CETOL LOGSID TEAK SIK42085  
**Manufacturer** : PPG Architectural Finishes, Inc.  
 15885 West Sprague Road  
 Strongsville, OH 44136  
 U.S.A.  
**Validation date** : **2013-10-24.**  
**Print date** : 2013-10-24.  
**Responsible name** : Product Stewardship, Regulatory Affairs & Labeling  
**In case of emergency** : 1-800-545-2643

## 2. Hazards identification

### Emergency overview

**Physical state** : Liquid.

**Signal word** : WARNING!

**Hazard statements** : COMBUSTIBLE LIQUID AND VAPOR. HARMFUL IF SWALLOWED. CAUSES RESPIRATORY TRACT, EYE AND SKIN IRRITATION. MAY BE HARMFUL IF ABSORBED THROUGH SKIN. CONTAINS MATERIAL THAT MAY CAUSE TARGET ORGAN DAMAGE, BASED ON ANIMAL DATA. CANCER HAZARD - CONTAINS MATERIAL WHICH CAN CAUSE CANCER. NOTICE: This product contains solvents. Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

**Precautionary measures** : Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Do not eat, drink or smoke when using this product. Avoid contact with eyes, skin and clothing. Avoid prolonged contact with eyes, skin and clothing. Keep away from heat and flame. Keep container tightly closed. Use personal protective equipment as required. Wash thoroughly after handling.

### Potential acute health effects

**Inhalation** : Irritating to respiratory system.  
**Ingestion** : Toxic if swallowed.  
**Skin** : Harmful in contact with skin. Irritating to skin.  
**Eyes** : Irritating to eyes.

### Potential chronic health effects

**Chronic effects** : Contains material that may cause target organ damage, based on animal data. NOTICE: This product contains solvents. Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

**Carcinogenicity** : Contains material which can cause cancer. Risk of cancer depends on duration and level of exposure.

**Mutagenicity** : No known significant effects or critical hazards.

**Teratogenicity** : No known significant effects or critical hazards.

**Developmental effects** : No known significant effects or critical hazards.

**Fertility effects** : No known significant effects or critical hazards.

**Target organs** : Contains material which may cause damage to the following organs: blood, kidneys, the nervous system, liver, gastrointestinal tract, upper respiratory tract, skin, central nervous system (CNS), eye, lens or cornea, testes.

## 2. Hazards identification

### Over-exposure signs/symptoms

- Inhalation** : Adverse symptoms may include the following:  
respiratory tract irritation  
coughing
- Ingestion** : No specific data.
- Skin** : Adverse symptoms may include the following:  
irritation  
redness
- Eyes** : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness

See toxicological information (Section 11)

## 3. Composition/information on ingredients

Name	CAS number	%
Alkyd resin, n.o.s. (drying oil)		30-<60
Distillates (petroleum), hydrotreated light	64742-47-8	10-<30
Solvent naphtha (petroleum), medium aliph.	64742-88-7	5-<10
Silica gel, pptd., cryst.-free	112926-00-8	1-<5
Stoddard solvent	8052-41-3	1-<5
xylene	1330-20-7	1-<5
ETER DE GLICOL		1-<5
iron hydroxide oxide yellow	51274-00-1	1-<5
ethylbenzene	100-41-4	0.1-<1.0
cobalt bis(2-ethylhexanoate)	136-52-7	0.1-<1.0
ethanol	64-17-5	0.1-<1.0

## 4. First aid measures

- Eye contact** : Check for and remove any contact lenses. Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical attention immediately.
- Skin contact** : In case of contact, immediately flush skin with plenty of soap and water for at least 15 minutes while removing contaminated clothing and shoes. If any product remains, gently rub with petroleum jelly, vegetable or mineral/baby oil then wash again with soap and water. Repeat as needed. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention immediately.
- Inhalation** : Move exposed person to fresh air. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Loosen tight clothing such as a collar, tie, belt or waistband. Get medical attention immediately.
- Ingestion** : Wash out mouth with water. Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention immediately.

## 5. Fire-fighting measures

- Flammability of the product** : Combustible liquid. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion.
- Extinguishing media**
- Suitable** : Use dry chemical, CO<sub>2</sub>, water spray (fog) or foam.
- Not suitable** : Do not use water jet.
- Special exposure hazards** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
- Hazardous thermal decomposition products** : Decomposition products may include the following materials:  
carbon dioxide  
carbon monoxide  
metal oxide/oxides
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## 6. Accidental release measures

- Personal precautions** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 8).
- Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
- Methods for cleaning up**
- Small spill** : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Use spark-proof tools and explosion-proof equipment.
- Large spill** : Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Use spark-proof tools and explosion-proof equipment. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see section 1 for emergency contact information and section 13 for waste disposal.

## 7. Handling and storage

- Handling** : Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Avoid exposure - obtain special instructions before use. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use non-sparking tools. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container. Keep out of the reach of children.

## 7. Handling and storage

### Storage

: Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. Keep from freezing.

## 8. Exposure controls/personal protection

Ingredient	Exposure limits
Distillates (petroleum), hydrotreated light	<b>ACGIH TLV (United States, 1/2009). Absorbed through skin. Notes: Refers to Appendix A -- Carcinogens. Application restricted to conditions in which there are negligible aerosol exposures. ACGIH 2003 Adoption</b> TWA: 200 mg/m <sup>3</sup> 8 hour(s).
Solvent naphtha (petroleum), medium aliph.	<b>OSHA PEL 1989 (United States, 3/1989).</b> TWA: 100 ppm 8 hour(s). TWA: 400 mg/m <sup>3</sup> 8 hour(s). <b>OSHA PEL (United States, 6/2010).</b> TWA: 100 ppm 8 hour(s). TWA: 400 mg/m <sup>3</sup> 8 hour(s).
Silica gel, pptd., cryst.-free	<b>OSHA PEL 1989 (United States, 3/1989).</b> TWA: 6 mg/m <sup>3</sup> 8 hour(s). <b>NIOSH REL (United States, 6/2009).</b> TWA: 6 mg/m <sup>3</sup> 10 hour(s).
Stoddard solvent	<b>ACGIH TLV (United States, 1/2011). Notes: Substances for which the TLV is higher than the OSHA Permissible Exposure Limit (PEL) and/or the NIOSH Recommended Exposure Limit (REL). See CFR 58(124) :36338-33351, June 30, 1993, for revised OSHA PEL.</b> TWA: 525 mg/m <sup>3</sup> 8 hour(s). TWA: 100 ppm 8 hour(s). <b>NIOSH REL (United States, 6/2009).</b> CEIL: 1800 mg/m <sup>3</sup> 15 minute(s). TWA: 350 mg/m <sup>3</sup> 10 hour(s). <b>OSHA PEL (United States, 6/2010).</b> TWA: 2900 mg/m <sup>3</sup> 8 hour(s). TWA: 500 ppm 8 hour(s). <b>OSHA PEL 1989 (United States, 3/1989).</b> TWA: 525 mg/m <sup>3</sup> 8 hour(s). TWA: 100 ppm 8 hour(s).
xylene	<b>ACGIH TLV (United States, 1/2011). Notes: 1996 Adoption Substances for which there is a Biological Exposure Index or Indices Refers to Appendix A -- Carcinogens.</b> STEL: 651 mg/m <sup>3</sup> 15 minute(s). STEL: 150 ppm 15 minute(s). TWA: 434 mg/m <sup>3</sup> 8 hour(s). TWA: 100 ppm 8 hour(s). <b>OSHA PEL (United States, 6/2010).</b> TWA: 435 mg/m <sup>3</sup> 8 hour(s). TWA: 100 ppm 8 hour(s). <b>OSHA PEL 1989 (United States, 3/1989).</b> STEL: 655 mg/m <sup>3</sup> 15 minute(s). STEL: 150 ppm 15 minute(s). TWA: 435 mg/m <sup>3</sup> 8 hour(s). TWA: 100 ppm 8 hour(s).
ethylbenzene	<b>ACGIH TLV (United States, 1/2009). Notes: Substances for which there is a Biological Exposure Index or Indices 2002 Adoption.</b> STEL: 125 ppm 15 minute(s). <b>ACGIH TLV (United States, 1/2011). Notes: Substances for which</b>

## 8. Exposure controls/personal protection

ethanol	<p>there is a Biological Exposure Index or Indices 2002 Adoption. TWA: 20 ppm 8 hour(s).</p> <p><b>NIOSH REL (United States, 6/2009).</b> STEL: 545 mg/m<sup>3</sup> 15 minute(s). STEL: 125 ppm 15 minute(s). TWA: 435 mg/m<sup>3</sup> 10 hour(s). TWA: 100 ppm 10 hour(s).</p> <p><b>OSHA PEL (United States, 6/2010).</b> TWA: 435 mg/m<sup>3</sup> 8 hour(s). TWA: 100 ppm 8 hour(s).</p> <p><b>OSHA PEL 1989 (United States, 3/1989).</b> STEL: 545 mg/m<sup>3</sup> 15 minute(s). STEL: 125 ppm 15 minute(s). TWA: 435 mg/m<sup>3</sup> 8 hour(s). TWA: 100 ppm 8 hour(s).</p> <p><b>ACGIH TLV (United States, 1/2008). Notes: 1996 Adoption Refers to Appendix A -- Carcinogens.</b> TWA: 1880 mg/m<sup>3</sup> 8 hour(s).</p> <p><b>ACGIH TLV (United States, 1/2011). Notes: 1996 Adoption Refers to Appendix A -- Carcinogens.</b> STEL: 1000 ppm 15 minute(s).</p> <p><b>NIOSH REL (United States, 6/2009).</b> TWA: 1900 mg/m<sup>3</sup> 10 hour(s). TWA: 1000 ppm 10 hour(s).</p> <p><b>OSHA PEL (United States, 6/2010).</b> TWA: 1900 mg/m<sup>3</sup> 8 hour(s). TWA: 1000 ppm 8 hour(s).</p> <p><b>OSHA PEL 1989 (United States, 3/1989).</b> TWA: 1900 mg/m<sup>3</sup> 8 hour(s). TWA: 1000 ppm 8 hour(s).</p>
---------	---

- Recommended monitoring procedures** : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment.
- Engineering measures** : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.
- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
- Personal protection**
- Respiratory** : A NIOSH-approved, air-purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air-purifying respirators is limited. Use a positive-pressure, air-supplied respirator if there is any potential for uncontrolled release, exposure levels are not known or any other circumstances where air-purifying respirators may not provide adequate protection.
- Hands** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
- Eyes** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts.
- Skin** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

## 8. Exposure controls/personal protection

**Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

## 9. Physical and chemical properties

**Physical state** : Liquid.  
**Flash point** : Closed cup: 58°C (136.4°F)  
**Auto-ignition temperature** : Not available.  
**Flammable limits** : Not available.  
**Color** : Not available.  
**Odor** : not available  
**pH** : Not available.  
**Boiling/condensation point** : 157°C (314.6°F)  
**Melting/freezing point** : Not available.  
**Specific gravity** : 0.963  
**Density (lbs/gal)** : 8.036  
**Vapor pressure** : Not available.  
**Vapor density** : Not available.  
**Volatility** : 41.73% (v/v), 35.19% (w/w)  
**Viscosity** : Dynamic: 170 mPa·s (170 cP)  
**Dispersibility properties** : Not dispersible in the following materials: cold water.  
**Solubility** : Insoluble in the following materials: cold water.

## 10. Stability and reactivity

**Chemical stability** : The product is stable.  
**Conditions to avoid** : Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.  
**Incompatible materials** : Reactive or incompatible with the following materials:  
oxidizing materials  
**Hazardous decomposition products** : Under normal conditions of storage and use, hazardous decomposition products should not be produced.  
**Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.

## 11. Toxicological information

### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
xylene	LC50 Inhalation Gas.	Rat	5000 ppm	4 hours
	LD50 Dermal	Rabbit	>1700 mg/kg	-
ethylbenzene	LD50 Oral	Rat	4300 mg/kg	-
	LD50 Dermal	Rabbit	>5000 mg/kg	-
cobalt bis(2-ethylhexanoate)	LD50 Oral	Rat	3500 mg/kg	-
	LD50 Dermal	Rabbit	>5 g/kg	-
ethanol	LD50 Oral	Rat	1.22 g/kg	-
	LC50 Inhalation Vapor	Rat	124700 mg/m <sup>3</sup>	4 hours
	LD50 Oral	Rat	7 g/kg	-

**Conclusion/Summary** : Not available.

### Chronic toxicity

**Conclusion/Summary** : Not available.

### Irritation/Corrosion

# 11. Toxicological information

Product/ingredient name	Result	Species	Score	Exposure	Observation
Stoddard solvent	Eyes - Mild irritant	Human	-	100 parts per million	-
	Eyes - Moderate irritant	Rabbit	-	24 hours 500 milligrams	-
xylene	Eyes - Mild irritant	Rabbit	-	87 milligrams	-
	Eyes - Severe irritant	Rabbit	-	24 hours 5 milligrams	-
ethylbenzene	Skin - Mild irritant	Rat	-	8 hours 60 microliters	-
	Skin - Moderate irritant	Rabbit	-	24 hours 500 milligrams	-
	Skin - Moderate irritant Eyes - Severe irritant	Rabbit Rabbit	- -	100 Percent 500 milligrams	- -
ethanol	Skin - Mild irritant	Rabbit	-	24 hours 15 milligrams	-
	Eyes - Mild irritant	Rabbit	-	24 hours 500 milligrams	-
	Eyes - Moderate irritant	Rabbit	-	0.066666667 minutes 100 milligrams	-
	Eyes - Moderate irritant	Rabbit	-	100 microliters	-
	Eyes - Severe irritant	Rabbit	-	500 milligrams	-
	Skin - Mild irritant	Rabbit	-	400 milligrams	-
	Skin - Moderate irritant	Rabbit	-	24 hours 20 milligrams	-

**Conclusion/Summary** : Not available.

**Sensitizer**

**Conclusion/Summary** : Not available.

**Carcinogenicity**

**Conclusion/Summary** : Not available.

**Classification**

Product/ingredient name	ACGIH	IARC	EPA	NIOSH	NTP	OSHA
Distillates (petroleum), hydrotreated light	A3	-	-	None.	-	-
Silica gel, pptd., cryst.-free	-	3	-	-	-	-
Stoddard solvent	-	-	-	None.	-	-
xylene	A4	3	-	None.	-	-
ethylbenzene	A3	2B	-	None.	-	-
cobalt bis(2-ethylhexanoate)	-	2B	-	-	-	-
ethanol	A3	1	-	None.	-	-

**Mutagenicity**

**Conclusion/Summary** : Not available.

**Teratogenicity**

**Conclusion/Summary** : Not available.

**Reproductive toxicity**

**Conclusion/Summary** : Not available.

## 12. Ecological information

**Ecotoxicity** : No known significant effects or critical hazards.

### Aquatic ecotoxicity

Product/ingredient name	Result	Species	Exposure
Distillates (petroleum), hydrotreated light xylene	Acute LC50 2200 ug/L Fresh water	Fish - Lepomis macrochirus - 35 to 75 mm	4 days
	Acute LC50 8.5 ppm Marine water	Crustaceans - Palaemonetes pugio - Adult	48 hours
	Acute LC50 3300 to 4093 ug/L Fresh water	Fish - Oncorhynchus mykiss - 0.6 g	96 hours
	Acute EC50 4600 ug/L Fresh water	Algae - Pseudokirchneriella subcapitata	72 hours
	Acute EC50 3600 ug/L Fresh water	Algae - Pseudokirchneriella subcapitata	96 hours
	Acute EC50 2930 to 4400 ug/L Fresh water	Daphnia - Daphnia magna - Neonate - <=24 hours	48 hours
	Acute LC50 >5200 ug/L Marine water	Crustaceans - Americamysis bahia - <24 hours	48 hours
ethylbenzene	Acute LC50 4200 ug/L Fresh water	Fish - Oncorhynchus mykiss	96 hours
	Chronic NOEC 6800 ug/L Fresh water	Daphnia - Daphnia magna - <=24 hours	48 hours
	Chronic NOEC 3300 ug/L Marine water	Fish - Menidia menidia	96 hours
	Acute EC50 17.921 mg/L Marine water	Algae - Ulva pertusa	96 hours
	Acute EC50 2000 ug/L Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 25500 ug/L Marine water	Crustaceans - Artemia franchiscana - Larvae	48 hours
	Acute LC50 42000 ug/L Fresh water	Fish - Oncorhynchus mykiss	4 days
	Chronic NOEC <6.3 g/L Fresh water	Daphnia - Daphnia magna	48 hours
	Chronic NOEC 0.375 ul/L Fresh water	Fish - Gambusia holbrooki - Larvae - 3 days	12 weeks

**Conclusion/Summary** : Not available.



### Persistence/degradability

**Conclusion/Summary** : Not available.

## 13. Disposal considerations

Disposal should be in accordance with applicable regional, national and local laws and regulations. Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.

## 14. Transport information

Regulatory information	UN number	Proper shipping name	Classes	PG*	Label	Additional information
<b>DOT Classification</b>	UN1263	PAINT	3	III		-
<b>IMDG Class</b>	UN1263	PAINT	3	III		-

PG\* : Packing group



## 15. Regulatory information

- U.S. Federal regulations** : **United States inventory (TSCA 8b):** All components are listed or exempted.  
**SARA 302/304/311/312 extremely hazardous substances:** No components were found.  
**SARA 302/304 emergency planning and notification:** No components were found.  
**SARA 302/304/311/312 hazardous chemicals:** Distillates (petroleum), hydrotreated light; Stoddard solvent; xylene  
**SARA 311/312 MSDS distribution - chemical inventory - hazard identification:**  
 Distillates (petroleum), hydrotreated light: Delayed (chronic) health hazard; Stoddard solvent: Fire hazard, Immediate (acute) health hazard; xylene: Fire hazard, Immediate (acute) health hazard, Delayed (chronic) health hazard
- State regulations**
- Massachusetts** : The following components are listed: PRECIPITATED SILICA; STODDARD SOLVENT; XYLENE
- New York** : The following components are listed: Xylene (mixed); Ethylbenzene
- New Jersey** : The following components are listed: MINERAL SPIRITS; SOLVENT NAPHTHA (PETROLEUM) medium aliphatic; SILICA, AMORPHOUS, PRECIPITATE & GEL; STODDARD SOLVENT; XYLENES; BENZENE, DIMETHYL-; ETHYL BENZENE; BENZENE, ETHYL-; COBALT compounds; ETHYL ALCOHOL; ALCOHOL
- Pennsylvania** : The following components are listed: PRECIPITATED SILICA; STODDARD SOLVENT; BENZENE, DIMETHYL-; BENZENE, ETHYL-; COBALT COMPOUNDS; DENATURED ALCOHOL
- California Prop. 65**  
**WARNING:** This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

### International regulations

- Canada inventory** : Not determined.

## 16. Other information

**Hazardous Material Information System (U.S.A.)** :

Health	*	2
Flammability		2
Physical hazards		0

**Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.**

The customer is responsible for determining the PPE code for this material.

**Prepared by** : Product Stewardship, Regulatory Affairs & Labeling

### Notice to reader

The information contained herein is based on data available at the time of preparation of this data sheet and which PPG Architectural Finishes, Inc. believes to be reliable. However, no warranty is expressed or implied regarding the accuracy of this data. PPG Architectural Finishes, Inc. shall not be responsible for the use of this information, or of any product, method or apparatus mentioned and you must make your own determination of its suitability and completeness for your own use, for the protection of the environment, and the health and safety of your employees and users of this material.

Complies with OSHA Hazard Communication Standard 29CFR1910.1200.